

Figure 1




FIGURE 2

100




Figure 3

170




Figure 4

200

October 22, 1999

500

Solution Troubleshooting Resource - Netscape

File Edit View Go Communicator Help

Back Forward Reload Home Search Guide Print Security Shop

Bookmarks Location file:///C:/DDD/Working file/index.html

What's Related

CEC || CCO || SEARCH || INDEX || SUPPORT || FEEDBACK || DIRECTORY:  :Go

Solutions Delivery and Methodologies

Interactive Dynamic Documentation (ONLINE!)

CISCO SYSTEMS

201

Document Type

Select Document Type

Select your target solution

Select Target Solution

203

Set your search criteria

Use Defaults

Set Criteria

204

Ready!

205

General Information

Please Select

206

Quick Notes

207

Send Feedback

208

Document Done

209

Introduction?

210

\*CONTENT\* NEEDED \*PLEASE FEEL FREE TO CONTRIBUTE!!

211

Changing the way we work, play and learn

Are YOU ready?

202


FIGURE 5





FIGURE 6B

2007



203~  
204~

FIGURE 6C



2007

Solution Troubleshooting Resource - Netscape

File Edit View Go Communicator Help

Back Forward Reload Home Search Guide Print Security Shop Stop

What's Related

http://www.cisco.com/wwp/ipaddress/index.html

CEC || CCO || SEARCH || INDEX || SUPPORT || FEEDBACK || DIRECTORY:

Solutions Delivery and Methodologies

Interactive Dynamic Documentation (ONLINE!)



Document Type

Solution Troubleshooting Guide

Select your target solution

Select Target Solution

Select Target Solution

ThunderDial 2.1

Thunder Dial 2.2

Thunder Voice 2.1

Adagio

Ready!!

General Information

Please Select

Quick Notes

Send Feedback

Changing the way we  
work, play and learn

Are YOU ready?

Document Done

204 ~ →

FIGURE 6D






FIGURE 6F

200

003221 2284560

**Solution Troubleshooting Resource - Netscape**

File Edit View Go Print Home Help

Back Forward Home Stop Reload

http://www.rtpdev.cisco.com/sdebug/

Bookmark QuickFile

CEC || CCO || SEARCH || INDEX || SUPPORT || FEEDBACK || DIRECTORY: [ ] [Go]

**Solutions Delivery and Methodologies**

**Troubleshooting and Analysis Assistant**

**Thunder Dial 2.1 Solution Overview**

The Cisco SS7 Interconnect for Access Servers Solution is a distributed system used for interconnecting Cisco network access servers (NASSs) to a circuit-switched TDM network using Signaling System #7 (SS7) protocols for signaling. The interconnections are achieved using a protocol conversion platform called the Cisco Signaling Controller combined with the Cisco Signaling Link Terminal. The Cisco SC2200 comprises the hardware and software package that provides the signaling controller function in the Cisco SS7 Interconnect for Access Servers Solution. It provides high availability, high performance, and key scaling.

When large points of presence (POPs) receive calls from the Public Switched Telephone Network (PSTN), the traffic is running over legacy architectures. In-band signaling (such as Integrated Services Digital Network Primary Rate Interfaces (ISDN PRI)s) or single analog lines) rather than out-of-band signaling like SS7 is used. With both in-band channel-associated signaling (CAS), or single analog lines) rather than out-of-band signaling like SS7 is used. With both signaling and bearer traffic running over the lines, these legacy switches become congested with modem traffic and limited circuits. Cisco offers the Cisco SS7 Interconnect for Access Servers Solution that offloads the signaling to an out-of-band network so that available bandwidth increases.

The Cisco SS7 Interconnect for Access Servers Solution is a distributed system that adds SS7 signaling interfaces to large ISP POPs. SS7 interfaces are connected to the PSTN by using the same signaling technology as a PSTN switch. The Cisco SS7 Interconnect for Access Servers Solution consists of the Cisco signaling controller (also referred to as the Cisco SC2200 product), which includes the Cisco Signaling Link Terminal (Cisco SLT) and the network access server (NAS). The Cisco SS7 Interconnect for Access Servers Solution turns a POP into an end-office switching system in the PSTN, allowing direct peer-to-peer signaling connectivity. The POP, as a switch, connects directly to the rest of the network as a peer. After connections to the Internet are aggregated at a POP, streams of user packets are statistically multiplexed for efficient transport over the backbone network.

**General Topics**

Please Select

**Troubleshooting**

Please Select

**Sample Configurations**

Please Select

**Log and Alarm Descriptions**

Please Select

**Solution Components**

Please Select

**Client Scripts**

Please Select

**Reference Materials**

Please Select

**Search Feedback**

202

211

FIGURE 7A

FIGURE 8A

docbuilder/index.pl - Netscape

File Edit View Go Home Search Help

Back Forward Reload Home Search Guide Print Security Shop Stop

Bookmarks Location file:///C:/DDD/screenshot.htm

Document Builder

Document Type Troubleshooting Guide

Product Thunder Dial 2.1

Criteria SLT 12.1.3  
NAS 12.1.10  
MGC 7.4.1

805B ~ 1 MML Commands

806B ~ 2 Thunder Dial Solution Overview

807B ~ 3 Solution Hardware

808B ~ 4 Single and Dual Configuration

809B ~ 5 Verify Component Configuration

810B ~ 6 Checking Processes

802

803

804

4.1

4.1.1

4.2

4.2.1

4.2.2

4.2.3

6.0

6.1

6.2

Document Done

FIGURE 8B




FIGURE 9